

BID SCHEDULE FORM

Interior consultants are making cosmetic changes, which will be subjected to open book change orders of cost + 15%. Specs are design elements only. It is the responsibility of the contractor to include in their bid, everything necessary to accomplish specified designs. Where specified, contractor may not substitute with different product or "like" products.

ITEM NO	DESCRIPTION OF PHW IMPROVEMENTS	ROOM NUMBER	QTY	NOTES	APPROVAL INITIAL
1	Armstrong Striations BBT, T3601 Atmosphere, 12 in x 24 in. with high gloss floor wax finish applied after install. (Refer to product specs for appropriate wax). Must bid product specified No substitutions by contractors without written approval from design team.	All Rooms on 3 rd Floor and 3 rd Floor Vestibule		Direction of Layout TBD	
2	Baseboard: Mannington Commercial, Cetera 4 1/2", Cameo White 935 Must bid product specified No substitutions by contractors without written approval from design team.	All Rooms on 3 rd Floor /Vestibule and 1 st Floor and Vestibule			
3	Waiting room lobby ceiling Arktura, Atmosphere- Surf, white. With backlighting. Must bid product specified No substitutions by contractors without written approval from design team.	305			
4	Sinks for 3 rd floor bathroom off main waiting area and private offices will be Trueform Concrete SKU: FLO-20V-ADA, White Linen, no holes, support brackets. (see attached spec sheet) Must bid product specified No substitutions by contractors without written approval from design team.	341 342 340 344	4		
5.	Tile for shower for 3 rd floor bathroom private offices, Arizona Tile, 3D Blade White Matte, 12 x 22 for walls, floor mosaic tile. Must bid product specified No substitutions by contractors without written approval from design team.	340 344			
6	Green living wall on entire east lobby wall. Door to surgery center to be painted to blend into living wall. Door color and plant species TBD. Living wall provided by 3rd party, GC must include in bid, a water source and lighting (full spectrum grow lights) in soffit above.	105		Plumbing /lighting supplied by GC	
7	Doors from lobby to surgery center be flush mounted paint grade. (1 st Floor)	105	2		
8	Sinks for 3 rd floor bathroom (excluding restrooms specified in line item #4) DECORUM® WALL-HUNG LAVATORY WITH EVERCLEAN, no hole, color white. Must bid product specified No substitutions by contractors without written approval from design team.	325 326 329 330 310	5		
9	Wall mounted Purist, K-T11838,, with sensor for all exam room or SERIN® SENSOR-OPERATED PROXIMITY LAVATORY FAUCET WALL-MOUNT Must bid product specified No substitutions by contractors without written approval from design team.	325 326 329 330 310	5		
10	Wall mounted Memoirs K-T11838-CP, vibrant stainless, with sensor for bathrooms. Must bid product specified No substitutions by contractors without	341 342 340	4		

BID SCHEDULE FORM

Interior consultants are making cosmetic changes, which will be subjected to open book change orders of cost + 15%. Specs are design elements only. It is the responsibility of the contractor to include in their bid, everything necessary to accomplish specified designs. Where specified, contractor may not substitute with different product or "like" products.

	<i>written approval from design team.</i>	344			
11	3 rd Floor reception desk design and finishes TBD				
12	Exam room counters Corian Solid Surface, Gray Onyx with seamless integrated white sinks, square. Cabinet color to be Wilsonart Atlantis D25-60. Must bid product specified No substitutions by contractors without written approval from design team.	316 317 318 319 320 321 334 335 336 338			
13	Doors from elevator vestibule to be glass if possible (1 st and 3 rd Floor)				
14	Lobby design approved by principals. Inset LED lighting (white and multicolored) soffit ceiling and walls (see attached concept drawing, detailed drawing to come).	105			
15	All hardware finishes to be polished chrome.				
16	1 st Floor Lobby and elevator vestibule to be NeoLith Blanco Carrara BC01 Endmatch, 6mm, Silk with anti-slip treatment with inset Perla, Satin (See attached design). Must bid product specified No substitutions by contractors without written approval from design team.	105			
18					
19					
20					
21					
22					

--	--	--	--	--	--




3RD FLOOR OVERVIEW NTS




FLOORING	ARMSTRONG STRIATIONS BBT, T3601 ATMOSPHERE, 12"X24" W/ HIGH GLOSS FLOOR WAX FINISH APPLIED AFTER INSTALL. (REFER TO PRODUCT SPECS FOR APPROPRIATE WAX.)
BASEBOARD	MANNINGTON COMMERCIAL, CETERA 4.5" CAMEO WHITE 935
DOORS	GLASS
HARDWARE	ALL HARDWARE TO BE POLISHED CHROME.
WAITING ROOM CEILING (305)	ARKTURA, ATMOSPHERA-SURF, WHITE. WITH BACKLIGHTING.
EXAM ROOM COUNTERS (316, 317, 318, 319, 320, 321, 334, 335, 336, AND 338)	CORIAN SOLID SURFACE, GRAY ONYX WITH SEAMLESS INTEGRATED WHITE SINKS, SQUARE. CABINET COLOR TO BE WILSONART ATLANTIS D25-60.

SINKS (341,342,340, AND 344)	TRUEFORM CONCRETE SKU: FLO-20V-ADA, WHITE LINEN, NO HOLES, SUPPORT BRACKETS,
SHOWER TILE (340 AND 344)	ARIZONA TILE, 3D BLADE WHITE MATTE, 12"X22" FOR WALLS, FLOOR MOSAIC TILE.
SINKS (325,326,329, 330, AND 310)	DECORUM WALL-HUNG LAVATORY WITH EVERCLEAN, NO HOLE, COLOR WHITE.
FAUCETS (325,326, 329, AND 330,310)	WALL MOUNTED PURIST, K-T11838, WITH SENSOR FOR ALL EXAM ROOM OR SERIN SENSOR OPERATED PROXIMITY LAVATORY FAUCET WALL MOUNT.
FAUCETS (341, 342, 340, AND 344)	WALL MOUNTED MEMOIRS K-T11838-CP, VIBRANT STAINLESS, WITH SENSOR FOR BATHROOMS.



1ST FLOOR LOBBY
1/4" = 1'-0"

	FLOORING	NEOLITH BLANCO CARRARA BC01 ENDMATCH 6MM SILK WITH ANTI-SLIP TREATMENT WITH INSET PERLA SATIN.
A	EAST LOBBY WALL	GREEN LIVING WALL PLUMBING & LIGHTING SUPPLIED BY THE GENERAL CONTRACTOR. (SEE DRAWING) GREEN WALL SUPPLIED BY THIRD PARTY. COLOR TO BE DETERMINED.
B	WEST LOBBY WALL	BLUE GLASS (SEE DRAWING) GLASS SUPPLIED BY THIRD PARTY.
C	DOOR (SURGERY)	FLUSH MOUNTED PAINTED TO MATCH GREEN WALL
D	DOOR (VESTIBULE)	GLASS
E	DOOR	WEST FLUSH MOUNTED DOOR, COLOR TBD.
	CEILING	SOFFIT WITH INSET LED LIGHTING (SEE CONCEPT DRAWING)
	HARDWARE	ALL HARDWARE TO BE POLISHED CHROME.



PALMDALE
HEALTH
AND
WELLNESS

- | | |
|------|-------------------------------|
| (R) | Recessed |
| (F) | Standard Depth |
| (G) | Glass (Supplied by 3rd party) |
| (LG) | LED Grow Lights |
| (L) | LED Strip Lights |

ALL FLOORING IS FLUSH
Material change creates the shape.

About:

Atmosfera® Standard builds on Arktura's experience designing and manufacturing custom solutions to deliver a dynamic, scalable, and affordable family of modular ceiling systems. Choose from linear, organic, and faceted designs, offered in a wide range of colors. With modules available in Arktura's Soft Sound® acoustical material (100% PET plastic with up to 60% recycled content), Atmosfera® Standard can transform the aesthetics of your space while drastically reducing sound reverberation.



Modular & Dynamic



Acoustical Systems



Easy Installation




Open Versatility




Quick Ship Options



Performance & Sustainable Practices




+ PLAN



- 86% open in plan
- Open percentage allows for the installation of sprinklers from above or between fins (reference your local building codes)
- Cameras, sensors, sprinklers, and lighting can be concealed between fins


*All dimensions nominal

+ SECTIONAL ELEVATION



+ COMPONENT DIAGRAM

Part	Material	Dimensions	Color	Material Thickness
Fin	Soft Sound®	10 1/2" Deep	See Standard Color Chart	12 mm Soft Sound®
Rib	Steel	7'-6" L		12 GA Steel



*See Website for Soft Sound® Color Options and Wood Finishes
*Patented

FAUCET TRIM K-T11838

Features

- Brass construction
- Touchless™ wall-mounted faucet
- 0.5 gal/min (1.9 l/min) flow rate
- Insight adaptive infrared technology

ADA


CSA B651

OBC

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.18.1/CSA B125.1
- Energy Policy Act of 1992
- CE



Colors/Finishes

- CP: Polished Chrome
- VS: Stainless Steel

Accessories

- NA: None applicable

Specified Model

Model	Description	Colors/Finishes	
K-T11838	Faucet trim	<input type="checkbox"/> CP	<input type="checkbox"/> VS
Required Accessories			
K-11830-NA	Wall-mount valve	<input type="checkbox"/> NA	
Optional Accessories			
1160593	Small Spray 0.38 gal/min (1.44 l/min)– Insert only	<input type="checkbox"/> NA	
_____	Additional flow options are available (refer to the Price Book)	<input type="checkbox"/> NA	

Product Specification

The Touchless™ wall-mounted faucet trim shall be made of brass construction. Faucet trim shall have a 0.5 gal/min (1.9 l/min) flow rate. The valve shall feature insight adaptive infrared technology. Faucet trim shall be Kohler Model K-T11838-_____.


MEMIORS®

Installation Notes

Install this product according to the installation guide.

ADA, CSA B651, OBC compliant when installed to the specific requirements of these regulations.

The sensor roughing-in allows for installation to a back splash or thicker finished wall than the spout roughing-in.



Product Diagram

FLOATING CONCRETE SINKS

20" ADA FLOATING CONCRETE RAMP SINK

SKU: FLO-20V-ADA

- Size: 20" x 17" x 5" / R-1410 Sink ID: 14" x 10" x 5"
- This sink meets ADA Accessibility Guidelines
- 8 concrete color options
- 6" drain tailpiece included in Polished Chrome - available in 2 other finishes
- Standard Faucet Hole Configurations (customizable):
 - 0 Holes: wall-mount faucet
 - 1 single faucet hole or triple-hole set: centered on sink basin
 - Triple-hole set = 8" spread
 - Hole diameter = 1 3/8"
 - Hole(s) centered 2 1/4" off back of sink basin
- Sink does not have overflow hole
- Mounts to wall studs with 2 brackets (SKU: FSB-L-S, sold separately).
Refer to Bracket Mounting Instructions sheet for more details.
- Handmade in the USA

CONCRETE COLORS



Compliances & Certifications




ICC A117.1




CSA B45/IAPMO Z403
ASME A112.18.2/CSA B125.2

PLAN VIEW




RIGHT SECTION



REAR ELEVATION

L BRACKET LOCATION (SEE BRACKET MOUNTING INSTRUCTIONS)



Features

- 0.5 gal/min (1.9 l/min) flow rate.
- This is trim set only. It requires valve kit to complete the faucet.
- Vandal-resistant aerator.
- 9" (229 mm) spout reach.
- Less drain.
- Safe Drinking Water Act (SDWA- Low Lead) compliant.
- On demand on and off. Valve kit is factory set to 30 second max. continual run cycle if it turned on continuously.

Material

- Brass construction.

Technology

- Valve kit has electronic Insight™ Sensor Technology for accurate and consistent activation.
- This trim set can be used with 11830-NA (Hybrid power) wall mount valve or 11843-NA (AC Power) wall mount valve.

Installation

- Single-hole spout mounting. Please consider appropriate distance between spout and sensor.
- Below the counter valve for easy installation and maintenance.

Required Products/Accessories

K-11830 Wall-mount Valve for Touchless Faucets

or

K-11843 Wall-mount Valve for Touchless Faucets

Optional Products/Accessories

1160593 .35 gpm Aerator, Small



ADA

CSA B651

OBC

Codes/Standards

ASME A112.18.1/CSA B125.1

NSF/ANSI 372

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color Code Description



CP Polished Chrome



VS Vibrant® Stainless



Technical Information

All product dimensions are nominal.

Faucet:

Flow rate: 0.5 gal/min (1.9 l/min)


Pressure: 60 psi (4.1 bar)

Notes

Install this product according to the installation guide.

The sensor roughing-in allows for installation to a back splash or thicker finished wall than the spout roughing-in.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.



PRODUCT FEATURES:

- **Self-Adjusting Sensor:** Sensor automatically sets the activation range on start-up by evaluating sink size and other factors. Will adjust range to adapt to changes in the bathroom environment.
- **Sensor in Spout Tip:** Clean, streamlined style. Hidden sensor reduces vandalism.
- **Hygienic, touch-free operation**
- **Adjustable Spout Reach:** Easily adjustable from 6" - 9" (from the wall to the outlet).
- **Self-Cleaning Solenoid Reduces Maintenance:** Integral wiper spring prevents clogging and run-on.
- **Easy to Service Integrated Strainer:** Patented in-line strainer protects the solenoid from debris. Strainer is enclosed in removable debris cup for easy service.
- **Safety Timer:** Helps prevent vandalism by turning off the faucet if the sensor is blocked for 55 seconds.
- **Fail-Safe:** Faucet automatically shuts off upon loss of power or dead battery. Prevents costly excess water usage and potential flooding
- **Lead-Free:** Faucet contains $\leq 0.25\%$ total lead content by weighted average.

GENERAL DESCRIPTION:

Wall-mount electronic faucet with proximity operation. Vandal-resistant brass construction. Operates on DC (battery) or AC permanent power. Water pressure range from 20 - 120 psi. Single inlet. Includes flexible hose and exposed elbow for connection from the spout to the control box.

MODEL NUMBER:

Rough Valve

- **R350** – Required for installation of all Serin wall-mount faucets.

Trim Kits



■ PWRX™ 10 YEAR BATTERY POWERED

- **T064.346** 0.35 gpm/1.3 L/min pressure compensating, vandal-resistant multi-laminar spray.
- **T064.345** 0.5 gpm/1.9 L/min pressure compensating, vandal-resistant multi-laminar spray.
- **T064.342** 1.5 gpm/5.7 L/min pressure compensating, vandal-resistant laminar flow outlet.

■ DC (CR-P2 LITHIUM BATTERY) POWERED

- **T064.356** 0.35 gpm/1.3 L/min pressure compensating, vandal-resistant multi-laminar spray.
- **T064.355** 0.5 gpm/1.9 L/min pressure compensating, vandal-resistant multi-laminar spray.
- **T064.353** 1.5 gpm/5.7 L/min pressure compensating, vandal-resistant laminar flow outlet.

■ OPTIONAL Thermostatic Mixing Valve

- **605XTMV1070** Thermostatic mixing valve, 20" long flexible inlet hoses with 3/8" compression fitting. ASSE 1070 certified down to 0.35 gpm/1.3 L/min.

■ OPTIONAL Remote Control

- **605XRCT** Adjusts setup parameters and allows for customization of functions. Can be used to program all Selectronic faucets and flush valves.

POWER OPTIONS:

- **PWRX 10 Year Battery System:** Battery Life - 480,000 cycles (10 years @ 4,000 cycles per month). Advanced battery & electronics reduce the downtime and maintenance costs associated with changing batteries. Safety Circuitry prevents overheating in case of short circuit and protects the electronics from damage.
- **DC:** CR-P2 lithium battery. Battery Life - 192,000 cycles (4 years @ 4,000 cycles per month).



PWRX®



ADA COMPLIANT



LEAD FREE



WATER
EFFICIENT

RECOMMENDED SPECIFICATION:

Electronic, sensor-operated proximity lavatory faucet shall feature vandal-resistant brass body with wall-mount design. Single inlet. Adjustable spout reach from 6" – 9". Shall also feature a low energy use electronically operated, self cleaning solenoid valve with an in-line strainer, and microprocessor controlled proximity sensors. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Model shall be American Standard # R350 & T064.3____.

CODES AND STANDARDS



These products meet or exceed the following codes and standards:

ANSI A117.1
ASME A112.18.1
CSA B 125
NSF 372

ADA Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for accessible and usable building facilities - check local codes

Finishes

Polish Chrome	.002
Brushed Nickel	.295



**DECORUM® WALL-HUNG LAVATORY
WITH EVERCLEAN®**

- 20" x 18" vitreous china lavatory with EverClean included
- Available with rear overflow or less overflow
- Recessed self-draining deck with minimal backsplash
- For concealed arm or wall support (wall hanger included)
- ADA and TAS compliant
- Shown with Serin faucets (sold separately)
- Shown with drain grid (sold separately)

- ☐ **9024.000EC** No faucet holes
- ☐ **9024.001EC** Center hole only (CHO)
- ☐ **9024.021EC** CHO with left hand soap dispenser
- ☐ **9024.011EC** CHO with right hand soap dispenser
- ☐ **9024.901EC** CHO less overflow
- ☐ **9024.921EC** CHO with left hand soap dispenser less overflow
- ☐ **9024.911EC** CHO with right hand soap dispenser less overflow
- ☐ **9024.004EC** 4" centers
- ☐ **9024.024EC** 4" centers with left hand soap dispenser
- ☐ **9024.014EC** 4" centers with right hand soap dispenser
- ☐ **9024.904EC** 4" centers less overflow
- ☐ **9024.924EC** 4" centers with left hand soap dispenser less overflow
- ☐ **9024.914EC** 4" centers with right hand soap dispenser less overflow
- ☐ **9024.008EC** 8" centers
- ☐ **9024.908EC** 8" centers less overflow

Nominal Dimensions:

464mm (18-1/4") deep, 508mm (20") wide

Bowl sizes:

354mm (13-15/16") wide, 325mm (12-13/16") front to back, 127mm (5") deep

To Be Specified:

- ☐ Color: ☐ White
- ☐ Faucet*:
- ☐ Faucet Finish:
- ☐ Supplies:
- ☐ 1-1/4" Trap:
- ☐ Suggested carriers include Jay R. Smith models 0801 and 0700

* See faucet section for additional models available

**Compliance Certifications -
Meets or Exceeds the Following Specifications:**

- ASME A112.19.2 for Vitreous China Fixtures



9024.001EC shown with 2064 Series Serin Faucet




9024.000EC shown with R350 & T064 Series Serin Faucet

SEE NEXT PAGE FOR ROUGHING-IN DIMENSIONS



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDE-
LINES AND ANSI A117.1 ACCESSIBLE AND USABLE
BUILDINGS AND FACILITIES - CHECK LOCAL CODES.
Top of front rim mounted 864mm (34") from finished floor.



NOTES:

● LOOSE KEY ANGLE STOPS, LESS WALL ESCUTCHEONS. SUPPLIES REQUIRED.
 DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED.
 ■ SUITABLE FOR REINFORCEMENT ONLY, ACTUAL DIMENSIONS MUST BE TAKEN FROM FIXTURE.
 FITTINGS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.
 PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL SUPPORTS.
 INSTALLATION INSTRUCTIONS SUPPLIED WITH LAVATORY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.



Model 9024.000EC
No Faucet Holes



Model 9024.001EC
Center Hole Only (CHO)



Model 9024.004EC
4" Centers



Model 9024.008EC
8" Centers



Model 9024.011EC
CHO With Right Hand Soap Dispenser



Model 9024.014EC
4" Centers With Right Hand Soap Dispenser



Model 9024.021EC
CHO With Left Hand Soap Dispenser



Model 9024.024EC
4" Centers With Left Hand Soap Dispenser



Model 9024.901EC
CHO Less Overflow



Model 9024.904EC
4" Centers Less Overflow



Model 9024.908EC
8" Centers Less Overflow



Model 9024.911EC
CHO With Right Hand Soap Dispenser
Less Overflow



Model 9024.914EC
4" Centers With Right Hand Soap Dispenser
Less Overflow



Model 9024.921EC
CHO With Left Hand Soap Dispenser
Less Overflow



Model 9024.924EC
4" Centers With Left Hand Soap Dispenser
Less Overflow